750 liters tank i syrefast 316

99 000 SEK /st exkl moms

item available on order

Article type: brand new transport tank - type VC-SCO
Additional information: example picture
Volumetric volume (L): 750 L
Max. density P (kg/m³): 1.200
Ra inner weld: 0,80

Pressure in tank: ATM - atmosferic
Max. temperature (°C): 60 °C

PROCESSÖVERSKOTT AB

Rodervägen 57
891 78 Bonässund
info@processoverskott.se

Läs våra köpvillkor

Min. temperature (°C): -10 °C
Material wet parts: SS AISI 316L (V4A)
Model: vertical

Configuration: single-skin
Heat exchanger: no
Insulation: no
Mobile tank: yes
Top type: large seperat lid

Shape of tank: cylindrical
Bottom type: conical
Total discharge: yes
Fixation points: 4 casters
Valve: RVS 316L

Fixation point(s): RVS 304L
Suitable for food industry: yes
Documents included: yes, optional
Technical drawing included: yes
Registration plate on the tank: yes

Flange for agitator: no
CIP spray ball: no
Tank outlet: inside Ø 40 mm
Outlet type: DIN11851
Total outlet valve: no, optional

Agitator: no, optional
Top: 2 mm
Cylinder: 3 mm
Bottom: 3 mm
Distance from outlet to ground: 250 mm

Outer diameter tank: 960 mm
Total height of tank: 1.520 mm
Empty weight tank: 170

SKU: 376973

PROCESSÖVERSKOTT AB

Rodervägen 57
891 78 Bonässund
info@processoverskott.se

Läs våra köpvillkor

Mer information

Beskrivelse av produkt

Næringsmiddelgodkjent: Ja
Materiale: Syrefast 316
Modell: Vertikal
Nyprodusert/Brukt: Nyprodusert
Arbeidstrykk i tank:
Konfiguration: enkelthudet
Maks. arbeidstemperatur: 60 °C
Maksimal tetthet for produktet: 1200
Min. arbeidstemperatur: -10 °C
Mobil tank: Ja
Øvrig informasjon: eksempelbilde
Omrører: Nei
Ra innvendig sveis: 0,80
Tankens form: sylindrisk
Total uttapping:
Type bunn: konisk
Oppvarming/kjøling: Nei
Væskebelastet overflate: SS AISI 316L (V4A)
Volum i liter: 750

Utstyr

Flens for omrører: Nei
Merkeskilt: Ja
Næringsmiddelgodkjent: Ja
Tankutløp: innvendig Ø 40 mm
Teknisk tegning finnes: Ja
Utløpstype: DIN11851

PROCESSÖVERSKOTT AB

Rodervägen 57
891 78 Bonässund
info@processoverskott.se

Läs våra köpvillkor

Materialoversikt

Materiale: Syrefast 316
Festepunkt(er): RVS 304L

Tankdimensjoner

Mål utløp til bakken: 250 mm
Total høyde: 1520 mm
Ytre diameter: 960 mm

Tanktykkelse

Bunn: 3 mm
Sylinder: 3 mm
Topp: 2 millimeter

Mer

Isolert: Nei
Vekt: 170

PROCESSÖVERSKOTT AB

Rodervägen 57
891 78 Bonässund
info@processoverskott.se

Läs våra köpvillkor