

8100 liters tank i rustfritt stål 304



110 000 SEK /st exkl moms

Article type: brand new storage tank - type K-SL

Volumetric volume (L): 8.100 L

Max. density P (kg/m³): 1.200

Pressure in tank: ATM - atmosferic

Material wet parts: SS AISI 304 (V2A)

Model: vertical

Configuration: single-skin

Heat exchanger: no

Insulation: no

Mobile tank: no



Top type: conical 15 °

Shape of tank: cylindrical

Bottom type: conical 15 °

Total discharge: yes

Fixation points: 4 adjustable feet

Legs: Set of baseplates and adjusting pieces included

Manway(s): RVS 304

Gasket manway(s): EPDM

Valve: RVS 316L

Fixation point(s): RVS 304

Suitable for food industry: yes

Documents included: yes, optional

Technical drawing included: yes

Registration plate on the tank: yes

Flange for agitator: no

Number of manways: 1

Position of manway: at the top

Height manhole 1 (mm): 500 mm

CIP spray ball: no

Tank outlet: inside Ø 65 mm

Outlet type: DIN11851

Total outlet valve: no, optional

Adjustable legs: yes

Agitator: no, optional

Top: 1,50 mm

Cylinder: 1,50 mm

Bottom: 2 mm

Distance from outlet to ground: 250 mm

Outer diameter tank: 1.874 mm

Cylinder height: 2.750 mm

Feet height: 630 mm

Total height of tank: 3.870 mm

Empty weight tank: 800



SKU: 460920

Mer information

Beskrivelse av produkt

Næringsmiddelgodkjent: Ja

Materiale: Rustfritt stål 304

Modell: Vertikal

Nyprodusert/Brukt: Nyprodusert

Arbeidstrykk i tank:

Konfiguration: enkelthudet

Maksimal tetthet for produktet: 1200

Mobil tank: Nei, det er det ikke.

Omrører: Nei

Tankens form: sylindrisk

Total uttapping:

Type bunn: konisk 15 °.

Oppvarming/kjøling: Nei

Væskebelastet overflate: SS AISI 304 (V2A)

Volum i liter: 8100

Utstyr

Flens for omrører: Nei

Merkeskilt: Ja

Næringsmiddelgodkjent: Ja

Tankutløp: innvendig Ø 65 mm

Teknisk tegning finnes: Ja

Utløpstype: DIN11851



Materialoversikt

Materiale: Rustfritt stål 304

Festepunkt(er): RVS 304

Tankdimensjoner

Sylinderhøyde: 2750 mm

Høyde på ben: 630 mm

Mål utløp til bakken: 250 mm

Total høyde: 3 870 mm

Ytre diameter: 1 874 mm

Tanktykkelse

Bunn: 2 millimeter

Sylinder: 1,50 mm

Topp: 1,50 mm

Mer

Isolert: Nei

Vekt: 800