

8550 liters tank i syrefast 316



271 000 SEK /st exkl moms

Additional information: Pharmaceutical Chemistry; Support brackets made of Fe; flanges partly made of Fe

Volumetric volume (L): 8.550 L

Pressure in tank: pressure and vacuum

Max. pressure (Bar): 3,20 Bar



Min. pressure (Bar): 1 Bar

Max. temperature (°C): 200 °C

Configuration: single jacketed with heat-exchanger

Heat exchanger: yes

Insulation: no

Mobile tank: no

Total discharge: yes

Volume: 160 L

Max Overpressure: 6 Bar

Max onderdruk: 1 Bar

Max. working temperature: 200 °C

Type HE on the bottom: half pipe welded onto the outside of the innertank

Type HE on the cylinder: half pipe welded onto the outside of the innertank

Documents included: no

Technical drawing included: no

Registration plate on the tank: yes

Flange for agitator: no

Outlet of tank: flange DN150

Agitator: yes

Number of revolutions: 8.5 - 51

Power: 15

Top: 10 mm

Cylinder: 8 mm

Bottom: 8 mm

Internal diameter tank: 2.000 mm

Cylinder height: 2.200 mm

Total height of tank: 5.200 mm

Empty weight tank: 1.200

SKU: 487136



Mer information

Beskrivelse av produkt

Nyprodusert/Brukt: Brukt

Arbeidstrykk i tank: trykk og vakuum

Konfiguration: enkeltmantlet med varmeveksler

Maks. arbeidstemperatur: 200 °C

Mobil tank: Nei, det er det ikke.

Øvrig informasjon: Farmasøytisk kjemi; Støttebraketter laget av Fe; flenser delvis laget av Fe; vi kan ikke gi noen garantier for omrøreren

Omrører: Ja

Overtrykk: 3,20 bar

Total uttapping: Ja

Undertrykk (vakuum): 1 bar

Trykktank: Ja

Oppvarming/kjøling: Ja

Volum i liter: 8550

Utstyr

Dokument finnes: Nei

Flens for omrører: Nei

Merkeskilt: Ja

Teknisk tegning finnes: Nei, det er det ikke.

Tankdimensjoner

Sylinderhøyde: 2 200 mm

Innvendig diameter: 2 000 mm

Total høyde: 5 200 mm



Omrører

Effekt (kW): 15

Turtall: 8.5 – 51

Tanktykkelse

Bunn: 8 millimeter

Sylinder: 8 millimeter

Topp: 10 mm

Mer

Isolert: Nei

Vekt: 1.200