

85700 liter tank i rustfritt stål 304



554 000 SEK /st exkl moms

item available on order

Article type: brand new storage tank

Additional information:

THE TANKS ARE NOT COMPLETELY READY - PROJECT CANCELLATION - FOR THE INDICATED PRICE THEY CAN BE FINISHED IN SHORT TERM --> 5 TANKS ARE COMPLETELY READY. The conical head side is AISI 316L the rest is AISI 304L. Agitator is not included. Several heating/cooling zones can be added to the tanks at €2,750 each, the heat exchangers can also be insulated separately with 50mm PU or 50mm rockwool and stainless steel welded cladding at €3,750 each.



Volumetric volume (L): 85.700 L

Max. density P (kg/m³): 1.100

Ra inner weld: 1,60

Finish stainless steel: 2R

Pressure in tank: ATM - atmosferic

Max. temperature (°C): 50 °C

Min. temperature (°C): -10 °C

Material wet parts: SS AISI 304L (V2A)

Model: vertical

Configuration: single jacketed with heat-exchanger

Heat exchanger: yes

Insulation: no

Mobile tank: no

Top type: conical 20

Shape of tank: cylindrical

Bottom type: flat sloping 3 %

Bottom outlet: yes

Total discharge: yes

Fixation points: attachment points

Type of HE on the cylinder: heating/cooling jacket

Height HE: 2.500 mm

Number of sections: 2

Height per section: 1.250 mm

Water pressure HE: 5 Bar

Contact surface cylinder: 23,20 m²

Working temperature HE cylinder: 50 °C

Heat exchanger: RVS 304

Manway(s): RVS 304L

Fixation point(s): RVS 304L

Suitable for food industry: yes

Documents included: yes, optional

Technical drawing included: yes

Registration plate on the tank: yes



Flange for agitator: no
Number of manways: 2
Position of manway: cylinder
Height manhole 1 (mm): 340 mm x H 440 mm
Position 2nd manway: headside

Tank outlet: inside Ø
Outlet type: DIN11851 male
Outlet of tank: 65
Tank location: inside a building
Agitator: no, optional

Top: 3 mm
Bottom: 3 mm
Outer diameter tank: 3.000 mm
Cylinder height: 12.000 mm
Total height of tank: 12.847 mm

Empty weight tank: 2.985

SKU: 422420

Mer information



Beskrivelse av produkt

Næringsmiddelgodkjent: Ja

Materiale: Rustfritt stål 304

Modell: Vertikal

Nyprodusert/Brukt: Nyprodusert

Arbeidstrykk i tank:

Finish rustfritt stål: 2R

Konfiguration: enkeltmantlet med varmeveksler

Maks. arbeidstemperatur: 50 °C

Maksimal tetthet for produktet: 1100

Min. arbeidstemperatur: -10 °C

Mobil tank: Nei, det er det ikke.

Øvrig informasjon: TANKENE ER IKKE HELT KLARE – PROSJEKTAVBESTILLING – FOR DEN ANGITTE PRISEN KAN DE VÆRE FERDIGE PÅ KORT SIKT -> 5 TANKER ER HELT KLARE. Den koniske hodesiden er AISI 316L den

Omrører: Nei

Ra innvendig sveis: 1,60

Tankens form: sylindrisk

Total uttapping:

Type bunn: Flat helling 3 %.

Oppvarming/kjøling: Ja

Væskebelastet overflate: SS AISI 304L (V2A)

Volum i liter: 85700

Utstyr

Flens for omrører: Nei

Merkeskilt: Ja

Næringsmiddelgodkjent: Ja

Tankutløp: innvendig Ø

Teknisk tegning finnes: Ja

Utløpstype: DIN11851 hann

Materialoversikt

Materiale: Rustfritt stål 304

Festepunkt(er): RVS 304L



Tankdimensjoner

Sylinderhøyde: 12 000 mm

Total høyde: 12 847 mm

Ytre diameter: 3 000 mm

Varmevekslere

Arbeidstemperatur varmeveksler sylinder: 50 °C

Høyde varmeveksler: 2 500 mm

Kontaktflate sylinder: 23,20 m²

Type varmeveksler på sylinder: varme-/kjølekappe

Vanntrykk varmeveksler: 5 barer

Tanktykkelse

Bunn: 3 mm

Topp: 3 mm

Mer

Varmeveksler: RVS 304

Isolert: Nei

Vekt: 2.985