8890 liter tank i syrefast 316

548 000 SEK /st exkl moms

Additional information: Apparatus was manufactured for a global pharmaceutical company but never put into operation there; diameter of spout (fitting) approx. 44 mm
Volumetric volume (L): 8.890 L
Pressure in tank: pressure and vacuum
Max. pressure (Bar): 6 Bar

PROCESSÖVERSKOTT AB

Rodervägen 57
891 78 Bonässund
info@processoverskott.se

Läs våra köpvillkor

Min. pressure (Bar): 1 Bar

Max. temperature (°C): 150 °C
Material wet parts: SS AISI 316 (V4A)
Model: vertical
Configuration: insulated
Heat exchanger: no

Insulation: yes
Mobile tank: no
Total discharge: no
Volume: 143 L
Max Overpressure: 10 Bar

Max onderdruk: 1 Bar
Max. working temperature: 150 °C
Type HE on the cylinder: half pipe welded onto the outside of the innertank
Documents included: no
Technical drawing included: no

Registration plate on the tank: yes
Flange for agitator: no
Position of manway: headside
Top: 12,50 mm
Cylinder: 7,60 mm

Bottom: 9,50 mm
Internal diameter tank: 2.200 mm
Outer diameter tank: 2.400 mm
Total height of tank: 4.000 mm

SKU: 441419

Rodervägen 57
891 78 Bonässund
info@processoverskott.se

Mer information

Beskrivelse av produkt

Materiale: Syrefast 316
Modell: Vertikal
Nyprodusert/Brukt: Brukt
Arbeidstrykk i tank: trykk og vakuum
Konfiguration: isolert med varmeveksler
Maks. arbeidstemperatur: 150 °C
Mobil tank: Nei, det er det ikke.
Øvrig informasjon: Tanken ble produsert for et globalt farmasøytisk selskap, men ble aldri tatt i bruk; Diameter på utløp (fitting) ca. 44 mm; vi kan ikke gi noen garantier om varme-/kjølekappen
Øvrig informasjon2: jakke
Omrører: Nei
Overtrykk: 6 barer
Total uttapping: Ja
Undertrykk (vakuum): 1 bar
Trykktank: Ja
Oppvarming/kjøling: Ja
Væskebelastet overflate: SS AISI 316 (V4A)
Volum i liter: 8890

Utstyr

Dokument finnes: Nei, det er det ikke.
Flens for omrører: Nei
Merkeskilt: Ja
Teknisk tegning finnes: Nei, det er det ikke.

Materialoversikt

Materiale: Syrefast 316

Rodervägen 57
891 78 Bonässund
info@processoverskott.se

Tankdimensjoner
Innvendig diameter: 2 200 mm
Total høyde: 4 000 mm
Ytre diameter: 2 400 mm

Tanktykkelse
Bunn: 9,50 mm
Sylinder: 7,60 mm
Topp: 12,50 mm

Mer
Isolert: Ja

PROCESSÖVERSKOTT AB

Rodervägen 57
891 78 Bonässund
info@processoverskott.se

Läs våra köpvillkor