900 liters tank i syrefast 316

94 000 SEK /st exkl moms

Additional information: pharmacy; Filling pipe including spray head inside the vessel (see pictures); GEMÜ diaphragm valve at the outlet
Volumetric volume (L): 900 L
Pressure in tank: pressure and vacuum
Max. pressure (Bar): 3 Bar

PROCESSÖVERSKOTT AB

Rodervägen 57
891 78 Bonässund
info@processoverskott.se

Läs våra köpvillkor

Min. pressure (Bar): 1 Bar

Max. temperature (°C): 150 °C
Material wet parts: SS AISI 316 (V4A)
Model: vertical
Configuration: insulated
Heat exchanger: no

Insulation: yes
Mobile tank: no
Total discharge: yes
Volume: 54 L
Max Overpressure: 3 Bar

Max onderdruk: 1 Bar
Max. working temperature: 150 °C
Type HE on the cylinder: heating/cooling jacket
Heat exchanger: RVS 304
Documents included: no

Technical drawing included: no
Registration plate on the tank: yes
Flange for agitator: no
Position of manway: headside
Outlet of tank: DN25 DIN 11851

Internal diameter tank: 980 mm
Cylinder height: 850 mm
Total height of tank: 2.300 mm

SKU: 482329

PROCESSÖVERSKOTT AB

Rodervägen 57
891 78 Bonässund
info@processoverskott.se

Läs våra köpvillkor

Mer information

Beskrivelse av produkt

Materiale: Syrefast 316
Modell: Vertikal
Nyprodusert/Brukt: Brukt
Arbeidstrykk i tank: trykk og vakuum
Konfiguration: isolert med varmeveksler
Maks. arbeidstemperatur: 150 °C
Mobil tank: Nei, det er det ikke.
Øvrig informasjon: apotek; påfyllingsrør inkludert sprayhode inne i tanken (se bilder); GEMÜ-membranventil ved utløpet; vi kan ikke gi noen garantier for varme-/kjølekappen
Omrører: Nei
Overtrykk: 3 barer
Total uttapping: Ja
Undertrykk (vakuum): 1 bar
Trykktank: Ja
Oppvarming/kjøling: Ja
Væskebelastet overflate: SS AISI 316 (V4A)
Volum i liter: 900

Utstyr

Dokument finnes: Nei, det er det ikke.
Flens for omrører: Nei
Merkeskilt: Ja
Teknisk tegning finnes: Nei, det er det ikke.

Materialoversikt

Materiale: Syrefast 316

Tankdimensjoner

Sylinderhøyde: 850 mm
Innvendig diameter: 980 mm
Total høyde: 2 300 mm

PROCESSÖVERSKOTT AB

Rodervägen 57
891 78 Bonässund
info@processoverskott.se

Läs våra köpvillkor

Mer

Varmeveksler: RVS 304
Isolert: Ja

PROCESSÖVERSKOTT AB

Rodervägen 57
891 78 Bonässund
info@processoverskott.se

Läs våra köpvillkor