985 liters tank i syrefast 316

121 000 SEK /st exkl moms

Additional information: Pharmacy; Vessel is part of a pharmaceutical plant in a frame, Aisi 304; overall dimensions in the frame are partly estimated and may vary slightly
Volumetric volume (L): 985 L
Pressure in tank: pressure and vacuum
Max. pressure (Bar): 4 Bar

PROCESSÖVERSKOTT AB

Rodervägen 57
891 78 Bonässund
info@processoverskott.se

Läs våra köpvillkor

Min. pressure (Bar): 1 Bar

Max. temperature (°C): 150 °C
Material wet parts: SS AISI 316 (V4A)
Model: vertical
Configuration: insulated with heat-exchanger
Heat exchanger: yes

Insulation: yes
Mobile tank: no
Total discharge: yes
Volume: 82 L
Max Overpressure: 6 Bar

Max onderdruk: 1 Bar
Max. working temperature: 150 °C
Type HE on the bottom: heating/cooling jacket
Type HE on the cylinder: heating/cooling jacket
Documents included: no

Technical drawing included: no
Registration plate on the tank: yes
Flange for agitator: no
Outlet of tank: DN50 DIN 11851
Agitator: yes

Power: 0,55
Internal diameter tank: 880 mm
Outer diameter tank: 1.000 mm
Total height of tank: 2.950 mm
Total outer width: 1.400 mm

Total outer length: 3.000 mm

SKU: 440720-1

Rodervägen 57
891 78 Bonässund
info@processoverskott.se

Mer information

Beskrivelse av produkt

Materiale: Syrefast 316
Modell: Vertikal
Nyprodusert/Brukt: Brukt
Arbeidstrykk i tank: trykk og vakuum
Konfiguration: isolert med varmeveksler
Maks. arbeidstemperatur: 150 °C
Mobil tank: Nei, det er det ikke.
Øvrig informasjon: Apotek; Fartøyet er en del av et farmasøytisk anlegg i en ramme, Aisi 304; de totale målene i rammen er delvis estimert og kan variere noe; vi kan ikke gi noen garantier om
Øvrig informasjon2: varme-/kjølekappe; vi kan ikke gi noen garantier for omrøreren
Omrører: Ja
Overtrykk: 4 barer
Total uttapping: Ja
Undertrykk (vakuum): 1 bar
Trykktank: Ja
Oppvarming/kjøling: Ja
Væskebelastet overflate: SS AISI 316 (V4A)
Volum i liter: 985

Utstyr

Dokument finnes: Nei, det er det ikke.
Flens for omrører: Nei
Merkeskilt: Ja
Teknisk tegning finnes: Nei, det er det ikke.

Materialoversikt

Materiale: Syrefast 316

Rodervägen 57
891 78 Bonässund
info@processoverskott.se

Tankdimensjoner
Innvendig diameter: 880 mm
Total høyde: 2 950 mm
Ytre diameter: 1.000 mm

Omrører
Effekt (kW): 0,55

Mer
Isolert: Ja

PROCESSÖVERSKOTT AB

Rodervägen 57
891 78 Bonässund
info@processoverskott.se

Läs våra köpvillkor